



30872 Huntwood Ave., Unit #6  
Hayward, CA 94544  
(510) 471-3026  
www.billetboys.com

## INSTALLATION INSTRUCTIONS

### Rear fender tip light:

1. Remove taillight and disconnect the connector from the wiring module.
2. Disconnect connector for the stock fender tip light (above the taillight socket).
3. Push fender tip light connector through the taillight bezel and disconnect the wire from the clips on the underside of the fender.
4. Use a small screwdriver to pry the fender tip lens from the chrome surround utilizing the slot on the top of the lens. Note that both the surround and the lens are plastic so use care when prying.
5. Remove the fender tip assembly by unscrewing two screws holding it to fender. They are held by two nuts on the underside of the fender. (This hardware will not be reused.)
6. Drill out the two rivets holding the stock bulb holder and remove holder and wiring.
7. Insert wiring from LED circuit board through the fender tip surround and the hole near the bottom of fender.
8. Before attaching circuit board to fender, slide each of the thin plastic washers under the LEDs over the holes in the circuit board.
9. Use the following sequence to attach the LED circuit board to the fender: The screw goes through the thin plastic washer, the circuit board, the nylon spacer, the chrome plastic fender tip surround, the fender, a flat washer, and the nyloc nut. Adjust alignment of fender tip light assembly on the fender as necessary. Do not over tighten screws or the circuit board may be damaged.
10. Check to see that there is at least 1/16" clearance between the circuit board and the chrome plastic fender tip surround. Most LED failures are the result of the back of the circuit board contacting the chrome surface and shorting out the LEDs.
11. Insert wiring from circuit board through clips on inside of fender, through the fender and taillight bezel, and install connector in proper socket in the taillight module.
12. Install taillight wiring socket in the taillight module, turn on switch and check operation of running and brake lights. If everything works properly, reattach taillight assembly and reinstall the fender tip lens.

If you have any questions, please feel free to contact us at (925) 362-8220.